



| Номер подшипника | Размеры |    |    | Базовая нагрузка |           | Ограничение скорости |        |
|------------------|---------|----|----|------------------|-----------|----------------------|--------|
|                  | д:      | Д: | Б: | Кр(Н)            | Кукуруза) | Смазка               | Масло  |
| B.706.C          | 6       | 17 | 6  | 2.39             | 0.99      | 90000                | 155000 |
| B.706.AC         | 6       | 17 | 6  | 2.3              | 0.95      | 80000                | 135000 |
| HC.B.706.C       | 6       | 17 | 6  | 1.65             | 0.69      | 115000               | 180000 |
| HC.B.706.AC      | 6       | 17 | 6  | 1.58             | 0.69      | 95000                | 165000 |
| HS.706.C         | 6       | 17 | 6  | 1.59             | 0.9       | 110000               | 185000 |
| HS.706.AC        | 6       | 17 | 6  | 1.52             | 0.69      | 95000                | 160000 |
| HC.706.C         | 6       | 17 | 6  | 1.1              | 0.5       | 130000               | 210000 |
| HC.706.AC        | 6       | 17 | 6  | 1.06             | 0.48      | 115000               | 185000 |
| B.707.C          | 7       | 19 | 6  | 2.8              | 1.18      | 80000                | 135000 |
| B.707.AC         | 7       | 19 | 6  | 2.7              | 1.4       | 70000                | 115000 |
| HC.B.707.C       | 7       | 19 | 6  | 1.9              | 0.9       | 105000               | 175000 |
| HC.B.707.AC      | 7       | 19 | 6  | 1.75             | 0.79      | 90000                | 150000 |
| HS.707.C         | 7       | 19 | 6  | 1.9              | 0.9       | 105000               | 170000 |
| HS.707.AC        | 7       | 19 | 6  | 1.7              | 0.79      | 85000                | 145000 |
| HC.707.C         | 7       | 19 | 6  | 1.18             | 0.59      | 115000               | 180000 |
| HC.707.AC        | 7       | 19 | 6  | 1.14             | 0.56      | 105000               | 175000 |
| B.708.C          | 8       | 22 | 7  | 3.9              | 1.75      | 70000                | 115000 |
| B.708.AC         | 8       | 22 | 7  | 3.78             | 1.69      | 62000                | 95000  |
| HC.B.708.C       | 8       | 22 | 7  | 2.67             | 1.22      | 90000                | 155000 |
| HC.B.708.AC      | 8       | 22 | 7  | 2.58             | 1.18      | 75000                | 125000 |

### Miniature Angular Contact Bearings

|             |   |    |   |      |      |        |        |
|-------------|---|----|---|------|------|--------|--------|
| HS.708.C    | 8 | 22 | 7 | 1.95 | 1.1  | 90000  | 155000 |
| HS.708.AC   | 8 | 22 | 7 | 1.82 | 0.97 | 75000  | 125000 |
| HC.708.C    | 8 | 22 | 7 | 1.3  | 0.72 | 105000 | 175000 |
| HC.708.AC   | 8 | 22 | 7 | 1.25 | 0.68 | 85000  | 145000 |
| B.709.C     | 9 | 24 | 7 | 5.3  | 2.5  | 62000  | 95000  |
| B.709.AC    | 9 | 24 | 7 | 5.14 | 2.33 | 55000  | 85000  |
| HC.B.709.C  | 9 | 24 | 7 | 3.64 | 1.69 | 80000  | 130000 |
| HC.B.709.AC | 9 | 24 | 7 | 3.48 | 1.63 | 70000  | 115000 |
| HS.709.C    | 9 | 24 | 7 | 2.68 | 1.47 | 80000  | 135000 |
| HS.709.AC   | 9 | 24 | 7 | 2.52 | 1.39 | 70000  | 115000 |